

SQ 05.2 – SQ 14.2

Electrical data Part-turn actuators for open-close duty with 1-phase AC motors

Short-time duty S2 - 10 min, 220 V – 240 V/60Hz

Part-turn actuator			Motor										
Type	Operating time for 90° in seconds	Max. torque [Nm]	Motor type	Nominal power ¹⁾ P _N [kW]	Speed [rpm]	Operating capacitor ²⁾ [μF]	Nominal current ³⁾ I _N [A]	Max. current ⁴⁾ I _{max} [A]	Starting current I _A [A]	cos φ	Over-current protection device setting [A]	AUMA power class switchgear	
												Contact- tor	Thyristor
SQ 05.2	3	150	VW00063-2-0,06	0.06	3 360	16	1.3	1.9	7.4	0.94	1.9	A1	B1
	4.5						1.3	1.7	7.4	0.94	1.7	A1	B1
	6		VW00063-4-0,04	0.04	1,680	12	1.3	1.5	2.7	0.98	1.5	A1	B1
	9						1.3	1.5	2.7	0.98	1.5	A1	B1
	12		VW00063-4-0,02	0.02	1,680	8.0	1.0	1.1	2.5	0.80	1.1	A1	B1
	17						1.0	1.1	2.5	0.80	1.1	A1	B1
	25		SW00063-4-0,01	0.01	1,680	8.0	1.0	1.0	2.5	0.76	1.0	A1	B1
50	1.0	1.0					1.1	0.99	1.0	A1	B1		
SQ 07.2	3	300	VW00063-2-0,12	0.12	3,360	25	2.4	3.4	7.6	0.91	3.4	A1	B1
	4.5						2.4	3.0	7.6	0.91	3.0	A1	B1
	6		VW00063-4-0,06	0.06	1,680	20	1.9	2.4	4.6	0.98	2.4	A1	B1
	9						1.9	2.3	4.6	0.98	2.3	A1	B1
	12		VW00063-4-0,03	0.03	1,680	12	1.2	1.4	2.7	0.98	1.4	A1	B1
	17						1.2	1.4	2.7	0.98	1.4	A1	B1
	25		SW00063-4-0,01	0.01	1,680	8.0	1.0	1.1	2.5	0.76	1.1	A1	B1
50	1.0	1.0					1.1	0.99	1.1	A1	B1		
SQ 10.2	6	450	VW00063-4-0,10	0.10	1,680	20	2.0	2.7	4.6	0.98	2.7	A1	B1
	9						2.0	2.8	4.6	0.98	2.8	A1	B1
	12		SW00063-4-0,06	0.06	1,680	16	1.5	2.0	4.3	0.96	2.0	A1	B1
	17	1.5					1.8	4.3	0.96	1.8	A1	B1	
	25	1.3					1.5	2.7	0.98	1.5	A1	B1	
	35	SW00063-4-0,04	0.04	1,680	12	1.3	1.5	2.7	0.98	1.5	A1	B1	
50	1.3					1.5	2.7	0.98	1.5	A1	B1		
SQ 12.2	9	900	VW00063-2-0,19	0.19	3,360	25	2.7	3.6	7.6	0.92	3.6	A1	B1
	12						2.0	2.7	4.6	0.98	2.7	A1	B1
	17		VW00063-4-0,10	0.10	1,680	20	2.0	2.8	4.6	0.98	2.8	A1	B1
	25	1.5					2.0	4.3	0.96	2.0	A1	B1	
	35	SW00063-4-0,06	0.06	1,680	16	1.5	2.0	4.3	0.96	2.0	A1	B1	
	50					1.3	1.5	2.7	0.98	1.5	A1	B1	
	75	SW00063-4-0,04	0.04	1,680	12	1.3	1.5	2.7	0.98	1.5	A1	B1	
108	1.3					1.5	2.7	0.98	1.5	A1	B1		
SQ 14.2	20	1,800	VW00063-2-0,19	0.19	3,360	25	2.7	3.6	7.6	0.92	3.6	A1	B1
	30						2.0	2.7	4.6	0.98	2.7	A1	B1
	40	VW00063-4-0,10	0.10	1,680	20	2.0	2.8	4.6	0.98	2.8	A1	B1	
	60					1.5	2.0	4.3	0.96	2.0	A1	B1	
	85	SW00063-4-0,06	0.06	1,680	16	1.5	2.0	4.3	0.96	2.0	A1	B1	

Notes on table

1) Nominal power P _N	Mechanical power output at motor shaft at running torque of part-turn actuator (corresponds to approx. 35 % of maximum torque). The consumed electrical power can be calculated using the following formula: $P = U \times I \times \cos \varphi$
2) Service/starting capacitor	For VW/SW motors, operating capacitors are integrated within the motor.
3) Nominal current I _N	Current at running torque
4) Max. current I _{max}	Current at maximum torque

Notes on installation and sizing																	
Motor data	Motor data is approximate. Due to usual manufacturing tolerances, there may be deviations from the values given.																
Motor protection	<p>To protect against overheating, thermostats or PTC thermistors are embedded in the motor windings.</p> <p>Actuators without integral controls (AUMA NORM): Thermostats or PTC thermistors have to be considered within the external controls (refer to terminal plan).</p> <p>Note: Failure to connect thermostats or PTC thermistors shall void the warranty for the motor.</p> <p>Rating of the thermostats</p> <table border="1"> <thead> <tr> <th colspan="2">AC current</th> <th colspan="2">DC current</th> </tr> </thead> <tbody> <tr> <td colspan="2">250 V, 50 – 60 Hz</td> <td>60 V</td> <td>1.0 A</td> </tr> <tr> <td>cos φ = 1</td> <td>2.5 A</td> <td>42 V</td> <td>1.2 A</td> </tr> <tr> <td>cos φ = 0.6</td> <td>1.6 A</td> <td>24 V</td> <td>1.5 A</td> </tr> </tbody> </table> <p>Actuators with AM or AC integral controls: Thermal motor protection is already integrated.</p>	AC current		DC current		250 V, 50 – 60 Hz		60 V	1.0 A	cos φ = 1	2.5 A	42 V	1.2 A	cos φ = 0.6	1.6 A	24 V	1.5 A
AC current		DC current															
250 V, 50 – 60 Hz		60 V	1.0 A														
cos φ = 1	2.5 A	42 V	1.2 A														
cos φ = 0.6	1.6 A	24 V	1.5 A														
Mains voltage, mains frequency	<p>Permissible variation of mains voltage: ±10 %</p> <p>Permissible variation of mains frequency: ±5 %</p>																
Terminal plan	<table border="1"> <thead> <tr> <th>Part-turn actuators</th> <th>Motor (type)</th> <th>Terminal plan</th> </tr> </thead> <tbody> <tr> <td>SQ 05.2 – SQ 14.2</td> <td>VW.../SW...</td> <td>TPA01R1AA-101-000</td> </tr> </tbody> </table> <p>For further information refer to "Technical data Part-turn actuators SQ 05.2 – SQ 14.2 for open-close duty with 1-phase AC motors"</p>	Part-turn actuators	Motor (type)	Terminal plan	SQ 05.2 – SQ 14.2	VW.../SW...	TPA01R1AA-101-000										
Part-turn actuators	Motor (type)	Terminal plan															
SQ 05.2 – SQ 14.2	VW.../SW...	TPA01R1AA-101-000															
Switchgear sizing	<p>For motor operation, reversing contactors (mechanically, electrically and electronically locked) or thyristors (electronically locked) can be used.</p> <p>Actuators without integral controls (AUMA NORM): Switchgear are supplied by the customer. We recommend specification of switchgear suitable for their rated operating power/motor power in compliance with the assigned AUMA power class.</p> <p>Switchgear assignment to AUMA power classes:</p> <table border="1"> <thead> <tr> <th rowspan="2">AUMA power class</th> <th rowspan="2">Reversing contactor Rated operating power acc. to EN 60947-4-1 Utilization category AC-3</th> <th colspan="2">Reversing contactor Motor power according to UL/CSA at</th> </tr> <tr> <th>480 V AC</th> <th>600 V AC</th> </tr> </thead> <tbody> <tr> <td>A1</td> <td>400 V AC 4.0 kW</td> <td>5.0 hp</td> <td>5.0 hp</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th rowspan="2">AUMA power class</th> <th rowspan="2">Thyristor Rated operating current acc. to EN 60947-4-2 Utilization category AC-53a</th> </tr> <tr> <th>400 V AC</th> </tr> </thead> <tbody> <tr> <td>B1</td> <td>6 A</td> </tr> </tbody> </table> <p>Actuators with AM or AC integral controls: Required switchgear in power classes A1 or B1 are directly integrated in AM or AC controls.</p>	AUMA power class	Reversing contactor Rated operating power acc. to EN 60947-4-1 Utilization category AC-3	Reversing contactor Motor power according to UL/CSA at		480 V AC	600 V AC	A1	400 V AC 4.0 kW	5.0 hp	5.0 hp	AUMA power class	Thyristor Rated operating current acc. to EN 60947-4-2 Utilization category AC-53a	400 V AC	B1	6 A	
AUMA power class	Reversing contactor Rated operating power acc. to EN 60947-4-1 Utilization category AC-3			Reversing contactor Motor power according to UL/CSA at													
		480 V AC	600 V AC														
A1	400 V AC 4.0 kW	5.0 hp	5.0 hp														
AUMA power class	Thyristor Rated operating current acc. to EN 60947-4-2 Utilization category AC-53a																
		400 V AC															
B1	6 A																